

TYPO3.TYPO3CR - Bug # 1484

Status:	Resolved	Priority:	Should have
Author:	Matthias Hörmann	Category:	
Created:	2008-09-09	Assigned To:	Matthias Hörmann
Updated:	2011-05-05	Due date:	
Subject:	Namespace columns are used to store URIs now but are only VARCHAR(255)		
Description	...but URIs can be up to 2048 characters according to most sources		

Associated revisions

Revision ccf6e16f - 2008-09-19 18:25 - Karsten Dambekalns

TYPO3CR: Implemented MySQL testing, vastly improved PostgreSQL testing and wrote install shell script.

- the SQL code contains key lengths for MySQL which are removed by all code that uses the SQL automatically if the database type is not mysql, fixes #1486
- namespace URIs are now stored in TEXT columns, fixes #1484
- MySQL gets it's ANSI_QUOTES option after connection setup in all places where connections are made
- install.sh allows fully automated setup of both production and test databases: MySQL, PostgreSQL, SQLite; calls fixpermissions.sh
- install.sh automatically calls web based database setup via lynx (could be wget if there are problems with the availability of lynx but lynx -dump gives more meaningful output)
- testdb.sh replaces the various db specific tools and is used by install.sh for testdb setup, also allows dumping and cleanup of test databases
- PHP code uses testdb.conf to read test database settings (all except sqlite currently)
- production and testing now use the same database schema file, multi-line statements are now supported by the storage helper too

Patch (mostly) by Matthias Hörmann.

History

#1 - 2008-09-12 15:58 - Matthias Hörmann

- *Assigned To set to Matthias Hörmann*

Resolved in patch sent to Karsten today

#2 - 2008-09-19 19:50 - Karsten Dambekalns

- *Status changed from New to Resolved*
- *% Done changed from 0 to 100*

Applied in changeset r1261.