

Core - Bug # 15888

Status:	Closed	Priority:	Should have
Author:	Alban Cousinie	Category:	Database API
Created:	2006-03-23	Assigned To:	Ingmar Schlecht
Updated:	2006-08-12	Due date:	
TYPO3 Version:	4.0		
PHP Version:	4		
Complexity:			
Is Regression:			
Sprint Focus:			
Subject:	Database analyzer fails creating some tables with MySQL 3.23		
Description			
<p>The install tool fails to create the tables listed below with MySQL 3.23 because the primary keys definitions in the tables below do not state NOT NULL.</p> <p>Thus when using the database analyzer update feature, an invisible SQL error is raised stating a PRIMARY key must be NOT NULL and the table creation fails. No error message is stated, but there are 2 symptoms to this problem :</p> <ul style="list-style-type: none">- the database analyser update page keeps saying some tables are missing although you just attempted to create them and it did not report any failure.- Once you attempt to login with the login page of the backend, a "Warning: mysql_fetch_assoc(): supplied argument is not a valid MySQL result resource in typo3_src_path/t3lib/class.t3lib_db.php on line 796" error is raised followed by many "Cannot modify header information " consequent warnings. As a result, and because of the missing tables, you are unable to login into the backend. <p>This affected the following table in my installation :</p> <p>be_sessions cache_hash cache_imagesizes sys_preview sys_refindex cache_pagesection cache_typo3temp_log cache_md5params fe_session_data fe_sessions</p> <p>I solved the problem by manually creating the tables into MySQL using the table definitions outputted in the "COMPARE" page of the database analyzer. Thus when seizing manually a table like :</p> <pre>CREATE TABLE cache_pagesection (page_id int(11) unsigned default '0', mpvar_hash int(11) unsigned default '0', content blob, tstamp int(11) unsigned default '0', PRIMARY KEY (page_id,mpvar_hash));</pre> <p>you should write :</p> <pre>CREATE TABLE cache_pagesection (page_id int(11) unsigned default '0' NOT NULL,</pre>			

```
mpvar_hash int(11) unsigned default '0' NOT NULL,  
content blob,  
tstamp int(11) unsigned default '0',  
PRIMARY KEY (page_id,mpvar_hash)  
);
```

(issue imported from #M2969)

Related issues:

duplicates Core - Bug # 15772: "NOT NULL" removed from SQL gives error with M...

Closed

2006-03-06

History