TYPO3.Flow - Task # 25605

Status:	Resolved	**Priority:**	Should have
Author:	Andreas Förthner	**Category:**	Core
Created:	2011-03-31	**Assigned To:**	Karsten Dambekalns
Updated:	2011-05-18	**Due date:**	

Sprint:	
PHP Version:	
Has patch:	
Complexity:	
Subject:	In the FLOW3 Bootstrap in handleCommandLineSlaveRequest() persistAll() should be triggered by a signal slot
Description	

See the Fixme in the code on line 289.

Associated revisions

Revision 6aee6d69 - 2011-05-17 15:52 - Karsten Dambekalns

[TASK] Command persistAll() after CLI slave request with signal

Change-Id: I797da23c81cefb580c31d9a358bfae0a5cb1e693
Resolves: #25605

History

#1 - 2011-04-27 13:49 - Karsten Dambekalns

- Status changed from New to Needs Feedback

- Assigned To set to Karsten Dambekalns

When we discussed this, we did agree on dispatching a signal after every dispatched request and wire that to a persist slot. Right?

#2 - 2011-05-17 15:51 - Karsten Dambekalns

- Tracker changed from Bug to Task

- Status changed from Needs Feedback to Accepted

#3 - 2011-05-17 15:52 - Mr. Hudson

Patch set 1 of change I797da23c81cefb580c31d9a358bfae0a5cb1e693 has been pushed to the review server.

It is available at http://review.typo3.org/2164

#4 - 2011-05-17 15:55 - Karsten Dambekalns

- Status changed from Accepted to Under Review

#5 - 2011-05-18 08:35 - Karsten Dambekalns

- Status changed from Under Review to Resolved

- % Done changed from 0 to 100

Applied in changeset commit:6aee6d69af36a22cb0ed7e41227030cf5fb72aaf.

Applied in changeset commit:6aee6d69af36a22cb0ed7e41227030cf5fb72aaf.