

TYPO3.TYPO3CR - Bug # 27181

Status:	Closed	Priority:	Must have
Author:	Sebastian Kurfuerst	Category:	Node handling
Created:	2011-06-01	Assigned To:	
Updated:	2011-09-20	Due date:	
Subject:	Moving of nodes should not duplicate content		
Description	<p>right now, the way moving of nodes is implemented has some drawbacks. If we have 5 nodes:</p> <ul style="list-style-type: none">- Node1 (Sorting:1)- Node2 (Sorting:2)- Node3 (Sorting:3)- Node4 (Sorting:4)- Node5 (Sorting:5) <p>and then we move Node5 before Node1, this will lead to a complete re-numbering:</p> <ul style="list-style-type: none">- Node5 (Sorting:1)- Node1 (Sorting:2)- Node2 (Sorting:3)- Node3 (Sorting:4)- Node4 (Sorting:5) <p>This will copy all nodes to personal workspace, although nothing changed.</p> <ul style="list-style-type: none">- An idea would be to distinguish between content changes and further changes like moving or deleting nodes.		

History

#1 - 2011-06-01 12:19 - Sebastian Kurfuerst

- Category set to Node handling
- Priority changed from Should have to Must have
- Target version set to Sprint 7

#2 - 2011-09-20 17:54 - Sebastian Kurfuerst

- Status changed from New to Closed

Bulk-closing issues because they are

- not relevant anymore due to the sproutcore based backend
- or already implemented in the meantime.

Regards, Sebastian