```
Priority:
Status:
                                                                                            Should have
                         Closed
Author:
                         Alain
                                                                   Category:
                                                                                            TypoScript
Created:
                         2012-01-16
                                                                   Assigned To:
Updated:
                        2012-02-07
                                                                   Due date:
TYPO3 Version:
                         4.6
PHP Version:
Complexity:
Is Regression:
Sprint Focus:
Subject:
                         Empty content object when select.pidInList=0 set in TS
Description
Hello.
I get an empty return value while rendering dropdown list for countries from the static_info_tables extension. I use following TS:
    lib.country = CONTENT
    lib.country {
     table = static_countries
       select {
        pidInList = 0
        orderBy = cn_short_en
        selectFields = uid,cn iso 3
    }
While tracking the SELECT query in tslib_content, I found out in tslib_content::getQuery() that the logical operator NOT (!) is used to
check all select proporties if they exist. This operator does not differ between 0 and empty.
    foreach($properties as $property) {
     if(!$conf[$property]) {
       unset($conf[$property]);
     }
Even select.pidInList = 0 is set in TS, the condition is fulfilled and $conf['pidInList'] is removed.
```

2015-08-04

In next step, \$conf['pidInList'] will be compared with "

if(!strcmp(\$conf['pidInList'], ")) {
 \$conf['pidInList'] = 'this';

}

and afterwards 'this' will be replaced with

```
$GLOBALS['TSFE']->contentPid
```

This leads to a wrong SQL-query because the ID of current page (4) is taken instead of the pid value (0) set in TS.

```
SELECT cn_iso_3, cn_short_en FROM static_countries WHERE static_countries.pid IN (4) AND static_countries.deleted=0
```

In my view, it would be more accurate if to use !isset() instead of NOT in the foreach loop. This will exclude the 0 value in TS.

```
foreach($properties as $property) {
    ...

- if(!$conf[$property]) {
    + if(!isset($conf[$property])) {
      unset($conf[$property]);
    }
}
```

Many thanks and best regards,

Alain

Related issues:

related to Core - Task # 57168: Enable queries using "root" and "-1" for pidl	Resolved	2014-03-21
duplicates Core - Bug # 32374: MENU special = updated not working in 4.6	Closed	2011-12-07
duplicates Core - Bug # 31209: CONTENT still can't select records from rootpage	Closed	2011-10-24

History

#1 - 2012-01-17 08:43 - Markus Klein

```
if(lisset($conf[$property])) {
  unset($conf[$property]);
}
```

seems to be a bit useless?!

#2 - 2012-01-22 01:06 - Jigal van Hemert

- Status changed from New to Needs Feedback

I think it has been fixed with https://review.typo3.org/#change,7839

It should have worked because of a special exception for static_* tables, and in current master (4.7-dev) it already works correctly. In 4.6.3 it didn't work for me.

Can you test if the mentioned change solves the problem for you?

2015-08-04 2/3

#3 - 2012-01-22 10:50 - Alain

Hello	Jigal,
I ICIIO	uiyai,

thanks for feedback.

I apply this patch in 4.6.3 and it works great for me.

The same patch is also available at https://review.typo3.org/#change,7826 but it is under review.

Best regards,

Alain

#4 - 2012-01-23 22:00 - Ernesto Baschny

- Category set to TypoScript
- Status changed from Needs Feedback to Closed
- Target version set to 4.6.4

Solution is already merged in #32374, so it will be available in 4.6.4 to be released soon. Thanks for your report and feedback!

2015-08-04 3/3