

TYPO3.Fluid - Bug # 3551

Status:	Resolved	Priority:	Should have
Author:	Joerg Schoppet	Category:	Core
Created:	2009-06-03	Assigned To:	Sebastian Kurfuerst
Updated:	2010-10-20	Due date:	
Has patch:			
Affected Flow version:			
Subject:	HtmlViewHelper outputs htmlspecialchars code		
Description			
Hi,			
using the HtmlViewHelper at least in typo3 4.3 the output is always htmlspecialchars.			
Adding:			
<code>\$value = htmlspecialchars_decode(\$value);</code>			
after line 71 of Tx_Fluid_ViewHelpers_Format_HtmlViewHelper			
solve this problem. But I don't know if this is the wanted way.			

History

#1 - 2009-06-04 09:49 - Bastian Waidelich

Note: The reason for this bug is the automatic htmlspecialchars'ing of object accessors introduced with <http://forge.typo3.org/repositories/revision/typo3v4-mvc/725>. We're planning to allow you to disable this in your view helpers. So the above solution is just preliminary.

#2 - 2009-06-05 09:41 - Sebastian Kurfuerst

We'll create a new variable inside a ViewHelper called "\$rawInput" which disables the postprocessing of ViewHelpers inside the opening / closing brackets.

If we have a viewhelper with rawInput=FALSE inside, then this should override the rawInput=TRUE.

\$rawInput will be marked as @internal first.

#3 - 2009-06-05 09:43 - Sebastian Kurfuerst

- Category changed from ViewHelpers to Core
- Status changed from New to Accepted
- Assigned To set to Sebastian Kurfuerst
- Target version set to 1.0.0 alpha 2
- Branch set to v4 + v5

#4 - 2009-06-12 13:54 - Sebastian Kurfuerst

- Status changed from Accepted to Resolved
- % Done changed from 0 to 100

resolved.