

TYPO3.Flow - Feature # 35965

Status:	Resolved	Priority:	Should have
Author:	Peter Russ	Category:	Security
Created:	2012-04-13	Assigned To:	Andreas Förthner
Updated:	2012-05-08	Due date:	
PHP Version:			
Has patch:	No		
Complexity:	easy		
Subject:	Session shouldn't start automatically		
Description			
<p>By default session handling is started automatically. This isn't useful when it comes to server/server communication.</p> <p>Places where it should be fixed:</p> <p>TYPO3\FLOW3\Security\Authentication\AuthenticationProviderManager line 130 * @FLOW3\Session(autoStart=true)</p> <p>and</p> <p>Package line 46/47</p> <pre>\$dispatcher->connect('TYPO3\FLOW3\Security\Authentication\AuthenticationProviderManager', 'authenticatedToken', 'TYPO3\FLOW3\Session\SessionInterface', 'renewId'); \$dispatcher->connect('TYPO3\FLOW3\Security\Authentication\AuthenticationProviderManager', 'loggedOut', 'TYPO3\FLOW3\Session\SessionInterface', 'destroy');</pre>			

Associated revisions

Revision ab61bd44 - 2012-05-07 14:56 - Andreas Förthner

[!!!][TASK] Change session autostart handling for authentication providers

The session autostart annotation is set at the providers, not at the authentication manager. By this every provider can decide on its own, if a session is needed or not.

Also adds a safeguard in the Session Logging Aspect to prevent errors while trying to log renewId() even though the session was not started yet.

Change-Id: Idea18525c2ac19f0d56b7ebb3b314009a2e93461

Releases: 1.1

Resolves: #35965

Revision 69c5912c - 2012-05-08 09:08 - Robert Lemke

[BUGFIX] Assure fresh session for functional tests

The changes done to resolve #35965 came with a functional test that worked fine when run in isolation but failed when run with other tests that would start a session.

This patch moves the \$session->destroy() call in the base test case from the tearDown() to the setUp()

method and fixes the behavior of destroy() in the TransientSession which did not reset the "started" flag.

Change-Id: I2fd85d24ef7456c84c9b36386a206c4c86a117bc
Related: #35965
Releases: 1.1

Revision a2033af0 - 2012-05-08 09:59 - Karsten Dambekalns

[BUGFIX] Adjust TransientSession unit test to recent change

The change in TransientSession to close the session when destroy() is called needed to be reflected in the unit test.

Change-Id: I4bb7b128ed934afa08223eb3aeae2f847f918a4
Related: #35965
Releases: 1.1

History

#1 - 2012-04-14 15:54 - Andreas Förthner

- *Project changed from TYPO3 Flow Base Distribution to TYPO3.Flow*

#2 - 2012-04-14 15:55 - Andreas Förthner

- *Category set to Security*
- *Has patch set to No*
- *Complexity set to easy*

#3 - 2012-04-14 15:56 - Gerrit Code Review

- *Status changed from New to Under Review*

Patch set 1 for branch **master** has been pushed to the review server.
It is available at <http://review.typo3.org/10469>

#4 - 2012-05-07 14:04 - Robert Lemke

Just for the record: it's not correct that sessions are generally started automatically - the "autostart" feature exists exactly for having more control over that behavior. What's right though is that the authenticate() method is starting a session because I did not consider authentication mechanisms which don't need sessions.

#5 - 2012-05-07 14:32 - Gerrit Code Review

Patch set 2 for branch **master** has been pushed to the review server.
It is available at <http://review.typo3.org/10469>

#6 - 2012-05-07 14:56 - Gerrit Code Review

Patch set 3 for branch **master** has been pushed to the review server.

It is available at <http://review.typo3.org/10469>

#7 - 2012-05-08 02:37 - Andreas Förthner

- *Status changed from Under Review to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset commit:ab61bd444fe1d2b1feb0e6e6a224575824fc7ce9.