

TYPO3.Flow - Bug # 36010

Status:	Closed	Priority:	-- undefined --
Author:	Uschi Renziehausen	Category:	- Error Handler Report -
Created:	2012-04-13	Assigned To:	Adrian Föder
Updated:	2012-05-25	Due date:	
PHP Version:	5.3		
Has patch:	No		
Complexity:			
Affected Flow version:	FLOW3 1.0.4		
Subject:	TYPO3\FLOW3\Exception thrown in file Bootstrap.php		
Description	<p>It seems like the PHP binary "C:\php\php" cannot be executed by FLOW3. Set the correct path to the PHP executable in Configuration/Settings.yaml, setting FLOW3.core.phpBinaryPathAndFilename.</p> <pre>3 TYPO3\FLOW3\Core\Bootstrap::initializeForRuntime() 2 TYPO3\FLOW3\Core\Bootstrap::handleWebRequest() 1 TYPO3\FLOW3\Core\Bootstrap::run()</pre> <p>I am using windows and the exeption above is thrown when I try to test my first steps with flow 3 according to http://flow3.typo3.org/documentation/quickstart.html > Testing the Installation.</p> <p>In Configuration/Settings.yaml I set phpBinaryPathAndFilename: 'E:\xampp\php\php.exe' and reloaded the page. The exeption is still there and still has C:\php\php, so perhaps the configuration is not read in which case this is a bug?</p> <p>The version I downloaded is Base Distribution (1.0.4) which I could not select.</p> <p>Regards Uschi</p>		

History

#1 - 2012-04-16 18:09 - Adrian Föder

- Assigned To set to Adrian Föder

Uschi, did you clear the caches (i.e. `rm -r Data/Temporary`) and tried running `./flow3.bat` again?

#2 - 2012-04-16 18:09 - Adrian Föder

- Status changed from New to Needs Feedback

#3 - 2012-04-16 23:25 - Sven Leuschner

Uschi - please tell us in WHICH directory did you change the settings.yaml

I found at least 2 locations

first one is Installation-Path->Configuration

second one in Installation-Path->Packages->Framework->TYPO.FLOW3->Configuration

If you make the changes in the second one it should work - at least it did for me

#4 - 2012-04-17 01:14 - Bastian Waidelich

Sven Leuschner wrote:

```
first one is Installation-Path->Configuration
second one in Installation-Path->Packages->Framework->TYPO.FLOW3->Configuration
```

You should not change the files inside the packages, otherwise you might run into conflicts when updating. Changing this in the global Configuration/Settings.yaml should work without having to flush the cache.

Make sure, that:

- your file is really called "Settings.yaml" (you have to rename "Settings.yaml.example")
- you comment out (remove the "#") from **both** affected lines
- the indentation is correct

The resulting file should look like:

TYPO3:

FLOW3:

persistence:

```
# It is good practice to not specify user name and password of the database
# connection in this global Settings.yaml file. Rather specify them in the
# settings of the respective context (Production / Development ...).
```

backendOptions:

```
host: '127.0.0.1' # adjust to your database host
```

```
# On Windows, you might need to uncomment the following lines and specify
# the location of the PHP binary manually.
```

core:

```
phpBinaryPathAndFilename: 'C:/path/to/php.exe'
```

#5 - 2012-04-18 11:13 - Bastian Waidelich

- Affected Flow version changed from FLOW3 1.0.3 to FLOW3 1.0.4

#6 - 2012-05-25 14:38 - Karsten Dambekalns

- Status changed from Needs Feedback to Closed