

TYPO3.TYPO3CR - Bug # 37434

Status:	Resolved	Priority:	Must have
Author:	Adrian Föder	Category:	Node handling
Created:	2012-05-23	Assigned To:	Adrian Föder
Updated:	2012-05-24	Due date:	
Subject:	Functional Domain/NodesTest must have testableHttpEnabled		
Description			
TYPO3\TYPO3\Domain\Service\Context::initializeObject() has \$activeRequesthandler->getHttpRequest()->getUri()->getHost() getHttpRequest() returns NULL if the TYPO3CR's NodesTest doesn't have protected \$testableHttpEnabled = TRUE; and therefore the FunctionalTest fatal error's very early with "calling getUri() on a Non-object"			

Associated revisions

Revision a9e150eb - 2012-05-23 15:13 - Adrian Föder

[BUGFIX] Functional Test Domain\NodesTest now has Http enabled

The NodesTest must have testableHttpEnabled set to TRUE in order to don't let the involved TYPO3.TYPO3\Domain\Service\Context fail.

Change-Id: Ia5df4743011b6e074a80e84e51a033ff938dac03

Fixes: #37434

History

#1 - 2012-05-23 15:13 - Gerrit Code Review

Patch set 1 for branch **master** has been pushed to the review server.

It is available at <http://review.typo3.org/11538>

#2 - 2012-05-23 23:54 - Christian Müller

- Status changed from New to Under Review

#3 - 2012-05-24 00:45 - Christian Müller

- Status changed from Under Review to Resolved