

TYPO3.Flow - Bug # 37445

Status:	Resolved	Priority:	Should have
Author:	Bastian Waidelich	Category:	MVC - Routing
Created:	2012-05-23	Assigned To:	Bastian Waidelich
Updated:	2012-05-30	Due date:	
PHP Version:			
Has patch:	No		
Complexity:			
Affected Flow version: Git master			
Subject:	Router overrides POST arguments		
Description			
I'm not sure whether this was introduced with #36913, but the POST/PUT arguments are currently not merged with the arguments set from the router but instead Router::route() overrides arguments with the same name.			
Related issues:			
related to TYPO3.Flow - Bug # 36913: HTTP PUT data not recognized as arguments		Resolved	2012-05-07

Associated revisions

Revision 170733fb - 2012-05-30 14:45 - Bastian Waidelich

[BUGFIX] Router overrides request arguments

With the reworked Request stack, the router kicks in after the action request have been built, overriding all arguments the respective route specifies.

This works for the most cases, but leads to issues when you try to specify part of a complex target argument via the route and part via request.

For example if you update a domain model via request body but specify the model itself through the URI like <http://domain/products/product-1> - now the Identity-RoutePart detects "product-1" and turns it into the corresponding __identity-array but then the Router kicks in and overrides the "product" argument completely resulting in a new object to be created by the property mapper.

This change adjusts the Router to recursively merge arguments with the route values instead, with precedence to the route values.

Change-Id: I22edc9e871b8b6e5baa731fe30e944f3e5575d05

Fixes: #37445

Releases: 1.1, 1.2

Revision 4ffcef32 - 2012-05-30 15:01 - Bastian Waidelich

[BUGFIX] Router overrides request arguments

With the reworked Request stack, the router kicks in after the action request have been built, overriding all arguments the respective route specifies.

This works for the most cases, but leads to issues when you try to specify part of a complex target argument via the route and part via request.

For example if you update a domain model via request body but specify the model itself through the URI like <http://domain/products/product-1> - now the Identity-RoutePart detects "product-1" and turns it into the corresponding __identity-array but then the Router kicks in and overrides the "product" argument completely resulting in a new object to be created by the property mapper.

This change adjusts the Router to recursively merge arguments with the route values instead, with precedence to the route values.

Change-Id: I22edc9e871b8b6e5baa731fe30e944f3e5575d05

Fixes: #37445

Releases: 1.1, 1.2

History

#1 - 2012-05-24 10:27 - Bastian Waidelich

- Category changed from MVC to MVC - Routing
- Status changed from New to Accepted
- Assigned To set to Bastian Waidelich

#2 - 2012-05-25 09:40 - Karsten Dambekalns

- Target version changed from 1.1 to 1.1 RC1

#3 - 2012-05-30 14:40 - Gerrit Code Review

- Status changed from Accepted to Under Review

Patch set 1 for branch **master** has been pushed to the review server.

It is available at <http://review.typo3.org/11732>

#4 - 2012-05-30 14:41 - Bastian Waidelich

- Target version changed from 1.1 RC1 to 1.1 beta 2

#5 - 2012-05-30 14:47 - Gerrit Code Review

Patch set 2 for branch **master** has been pushed to the review server.

It is available at <http://review.typo3.org/11732>

#6 - 2012-05-30 15:01 - Gerrit Code Review

Patch set 1 for branch **FLOW3-1.1** has been pushed to the review server.

It is available at <http://review.typo3.org/11735>

#7 - 2012-05-30 15:38 - Bastian Waidelich

- *Status changed from Under Review to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset commit:4ffcef32bca0ee9d05c743126ce9c4fd0904d726.