

TYPO3.Flow - Bug # 44185

Status:	New	Priority:	Should have
Author:	Bastian Waidelich	Category:	MVC
Created:	2012-12-21	Assigned To:	
Updated:	2013-08-14	Due date:	
PHP Version:			
Has patch:	No		
Complexity:			
Affected Flow version: Git master			
Subject:	XML body always need a root node		
Description			
<p>If the request contains xml and the Content-Type header is set to "*/xml" the client currently has to surround the XML with an additional root node (which is basically ignored):</p>			
<pre>curl -i -H "Accept: application/xml" -H "Content-Type: application/xml" -X POST -d "<anything><product><title>foo</title></product></anything>" http://localhost/products</pre>			
<p>Instead the root node should be omitted:</p>			
<pre>curl -i -H "Accept: application/xml" -H "Content-Type: application/xml" -X POST -d "<product><title>foo</title></product>" http://localhost/products</pre>			
<p>This could be achieved by replacing</p>			
<pre>1\$xmlElement = new \SimpleXMLElement(urldecode(\$body), LIBXML_NOERROR);</pre>			
<p>with</p>			
<pre>1\$xmlElement = new \SimpleXMLElement('<root>' . urldecode(\$body) . '</root>', LIBXML_NOERROR);</pre>			
<p>in <code>Http\Request::decodeBodyArguments()</code>.</p>			

History

#1 - 2013-08-14 15:35 - Karsten Dambekalns

- Target version changed from 2.0 to 2.0.1