## TYPO3.Fluid - Bug # 45384

Status:	New	Priority:	Must have
Author:	Benno Weinzierl	Category:	Widgets
Created:	2013-02-11	Assigned To:	
Updated:	2013-08-14	Due date:	
Has patch:	No		
Affected Flow vers	ion: Git master		
Subject:	Persisted entity object in widg	et-configuration cannot be dese	ialized (after reload)
Description			
The object gets serialized in the session and is accessable in a ajax-request (everything works).			
BUT:			
When i reload the page with the widget, the ajax calls fail with the following error:			
Fatal error: The script tried to execute a method or access a property of an incomplete object. Please ensure that the class			
definition "MyEntity" of the object you are trying to operate on was loaded <i>before</i> unserialize() gets called or provide a autoload()			
function to load the class definition in "my widget ajax action controller" on line 65			
I noticed that in Data/Temporary/Development/SubContextMyContext/Cache/Data/Flow_Session_Storage the entity is serialized.			
After reload the file contains the serialized entity two times. That seemes strange.			
History			
#1 - 2013-02-11 19:12 - Christian Müller			

I am not sure it is a good idea to try to add an entity to the widget context.

it should probably be represented only by it's identifier.

Generally I think it is a problem we should solve in the future (if possible), but a workaround might be to give only the identifier to the viewhelper and then in the ajax controller getting that object from persistence again.

## #2 - 2013-02-11 19:33 - Christian Müller

In order to be able to give an object to the viewhelper but serialize only the identifier you would have to overwrite the getAjaxWidgetConfiguration() method in your viewhelper (this in turn calls getWidgetConfiguration which you would need to overwrite too).

## #3 - 2013-08-14 15:35 - Karsten Dambekalns

- Target version changed from 2.0 to 2.0.1