

TYPO3.Flow - Bug # 46053

Status:	Resolved	Priority:	Must have
Author:	Thiago Colares	Category:	Log
Created:	2013-03-05	Assigned To:	Karsten Dambekalns
Updated:	2013-03-21	Due date:	
PHP Version:	5.3		
Has patch:	No		
Complexity:	easy		
Affected Flow version:	Flow 2.0.0 beta 1		
Subject:	Booting->initializeSystemLogger() uses a fixed \$loggerObjectName, rather than fetch it from Settings.yaml		
Description	<p>It should be set by Settings.yaml instead. So...</p> <p>File: \TYPO3\Flow\Core\Booting</p> <pre>/** * Initializes the System Logger * * @param \TYPO3\Flow\Core\Bootstrap \$bootstrap * @return void */ static public function initializeSystemLogger(Bootstrap \$bootstrap) { ... \$systemLogger = \TYPO3\Flow\Log\LoggerFactory::create('SystemLogger', 'TYPO3\Flow\Log\Logger', \$settings['log']['systemLogger']['backend'], \$settings['log']['systemLogger']['backendOptions']); ... }</pre> <p>Should something like</p> <pre>/** * Initializes the System Logger * * @param \TYPO3\Flow\Core\Bootstrap \$bootstrap * @return void */ static public function initializeSystemLogger(Bootstrap \$bootstrap) { ... \$systemLogger = \TYPO3\Flow\Log\LoggerFactory::create('SystemLogger', \$settings['log']['logger']['backend'], \$settings['log']['systemLogger']['backend'], \$settings['log']['systemLogger']['backendOptions']); ... }</pre> <p>Note: I'm using \$settings['log']['logger'] rather than 'TYPO3\Flow\Log\Logger'. Consequently, the Settings.yaml should be updated:</p> <p>TYPO3:</p>		

Flow:
log:
...
systemLogger:
...
logger: 'TYPO3\FLOW\Log\Logger'

Related issues:

related to TYPO3.Flow - Task # 47346: Configuration schema for doctrine cache...	Resolved	2013-04-18
duplicates TYPO3.Flow - Bug # 40738: Move System logger className to Settings...	Resolved	2012-09-07

Associated revisions

Revision 0c1046e9 - 2013-03-18 10:15 - Henrik Møller Rasmussen

[FEATURE] Make System Logger frontend configurable

Move hard coded TYPO3\FLOW3\Log\Logger to Settings.yaml instead. This allows a user to fully replace the logger instead of just adding or removing backends.

Resolves: #40738 #46053

Releases: master, 2.0

Change-Id: I6da4763fb94798b1d1647b6108457996a48aa128

Revision b1c23134 - 2013-03-21 15:18 - Henrik Møller Rasmussen

[FEATURE] Make System Logger frontend configurable

Move hard coded TYPO3\FLOW3\Log\Logger to Settings.yaml instead. This allows a user to fully replace the logger instead of just adding or removing backends.

Resolves: #40738

Resolves: #46053

Releases: master, 2.0

Change-Id: I6da4763fb94798b1d1647b6108457996a48aa128

Revision 8ece7498 - 2013-03-21 16:00 - Karsten Dambekalns

[BUGFIX] Undefined index breaks logger setup in Production

With I6da4763fb94798b1d1647b6108457996a48aa128 the logger used for the system log was made configurable. In Production context, when cached settings are used, this breaks after an update - and even --force with a cache flush does not help.

This change adds a safeguard against the settings not being there.

Change-Id: I3d72e8c8580f552f45a1865bd45dae01c4413cce

Related: #40738
Related: #46053
Releases: master, 2.0

Revision c3f0cdbf - 2013-03-21 16:05 - Karsten Dambekalns

[BUGFIX] Undefined index breaks logger setup in Production

With l6da4763fb94798b1d1647b6108457996a48aa128 the logger used for the system log was made configurable. In Production context, when cached settings are used, this breaks after an update - and even --force with a cache flush does not help.

This change adds a safeguard against the settings not being there.

Change-Id: I3d72e8c8580f552f45a1865bd45dae01c4413cce
Related: #40738
Related: #46053
Releases: master, 2.0

Revision 29ea4e4d - 2013-03-27 12:05 - Henrik Møller Rasmussen

[FEATURE] Make System Logger frontend configurable

Move hard coded TYPO3\FLOW3\Log\Logger to Settings.yaml instead. This allows a user to fully replace the logger instead of just adding or removing backends.

Resolves: #40738 #46053
Releases: master, 2.0
Change-Id: I6da4763fb94798b1d1647b6108457996a48aa128

Revision 60e1bd57 - 2013-03-27 12:05 - Karsten Dambekalns

[BUGFIX] Undefined index breaks logger setup in Production

With l6da4763fb94798b1d1647b6108457996a48aa128 the logger used for the system log was made configurable. In Production context, when cached settings are used, this breaks after an update - and even --force with a cache flush does not help.

This change adds a safeguard against the settings not being there.

Change-Id: I3d72e8c8580f552f45a1865bd45dae01c4413cce
Related: #40738
Related: #46053
Releases: master, 2.0

History

#1 - 2013-03-06 01:28 - Thiago Colares

- File 46053 added

#2 - 2013-03-06 10:58 - Karsten Dambekalns

- Category set to Log

#3 - 2013-03-18 10:05 - Karsten Dambekalns

- Status changed from New to Closed

- Assigned To set to Karsten Dambekalns

See #40738 for progress.

#4 - 2013-03-20 16:11 - Gerrit Code Review

- Status changed from Closed to Under Review

Patch set 2 for branch 2.0 has been pushed to the review server.

It is available at <https://review.typo3.org/19084>

#5 - 2013-03-21 16:13 - Gerrit Code Review

Patch set 3 for branch 2.0 has been pushed to the review server.

It is available at <https://review.typo3.org/19084>

#6 - 2013-03-21 17:37 - Henrik Møller Rasmussen

- Status changed from Under Review to Resolved

Applied in changeset commit:b1c23134f132bfce2b2eb828222b966d3e06e360.

Files

46053	2.4 kB	2013-03-06	Thiago Colares
-------	--------	------------	----------------