TYPO3.Flow - Bug # 4638

Status:	Resolved	**Priority:**	Should have
Author:	Sebastian Kurfuerst	**Category:**	
Created:	2009-09-15	**Assigned To:**	Sebastian Kurfuerst
Updated:	2010-10-20	**Due date:**	
PHP Version:			
Has patch:			
Complexity:			
Affected Flow version:			
Subject:	Refactor flash message implementation to use session scope		
Description			

We should move flash message handling from AbstractController to some separate object which is in the session scope and thus automatically persisted.
Additionally, this object can be put into the ControllerContext, so the API inside the Templates is nicer.

Associated revisions

Revision 22fd15cf - 2009-09-15 17:15 - Sebastian Kurfuerst

[!!!][~FEATURE] FLOW3 (MVC): Improved the way flash messages are handled. Now there is a separate "FlashMessages" object which encapsulates handling the flash messages. This removes $this->pushFlashMessage and $this->popFlashMessages inside the Controller and {flashMessages} inside Fluid Template. PLEASE UPGRADE by replacing "$this->pushFlashMessage(" with "$this->flashMessages->add(" inside your Controllers, and use <f:renderFlashMessages /> instead of the custom for loop inside your templates. Note: You can set a custom CSS class for outputting flash messages by using <f:renderFlashMessages class="..." /> inside your templates. Resolves #4638.

History

#1 - 2009-09-15 18:00 - Sebastian Kurfuerst

- *Status changed from Accepted to Resolved*
- *% Done changed from 0 to 100*

Applied in changeset r3175.