

TYPO3.Flow - Feature # 47137

Status:	Resolved	Priority:	Should have
Author:	Bastian Waidelich	Category:	Http
Created:	2013-04-11	Assigned To:	Bastian Waidelich
Updated:	2013-04-17	Due date:	
PHP Version:			
Has patch:	No		
Complexity:			
Subject:	HTTP method tunneling		
Description			
Due to limited support in browsers or restrictive firewalls, Flow should allow HTTP request methods to be overridden by the client.			
For POST requests the request method is overridden if			
<ul style="list-style-type: none">- a post argument __method is set OR- if the header X-HTTP-Method-Override is present OR- if the header X-HTTP-Method is present			
(first rule applies in the order specified)			
Example DELETE form:			
<pre>1<form method="POST"> 2 <input type="hidden" name="__method" value="DELETE" /> 3</form></pre>			
Related issues:			
related to TYPO3.Flow - Feature # 37604: Make Flow RestController useless by ...		Resolved	2012-05-30
related to TYPO3.Flow - Feature # 47551: Allow usage of links for destructive...		Rejected	2013-04-24

Associated revisions

Revision a297b170 - 2013-04-12 18:41 - Bastian Waidelich

[FEATURE] HTTP method tunneling

This change allows the HTTP method to be overridden by the client.

This is especially useful for clients that only support a subset of the supported methods (e.g. browsers).

The request method can be overridden by specifying a ``__method`` argument. Additionally Flow now respects the ``X-HTTP-Method`` respectively ``X-HTTP-Method-Override`` header.

usage::

```
&lt;form method="POST"&gt;
  &lt;input type="hidden" name="__method" value="DELETE" /&gt;
&lt;/form&gt;
```

Note::

The HTTP request method can only be changed for POST requests

Change-Id: Ibe753ca4bfcc3dc5b579e39fd13af95b79bc1f83

Resolves: #47137

Releases: master, 2.0

Revision f5b5024b - 2013-04-17 17:07 - Bastian Waidelich

[FEATURE] HTTP method tunneling

This change allows the HTTP method to be overridden by the client. This is especially useful for clients that only support a subset of the supported methods (e.g. browsers).

The request method can be overridden by specifying a ``__method`` argument. Additionally Flow now respects the ``X-HTTP-Method`` respectively ``X-HTTP-Method-Override`` header.

usage::

```
&lt;form method="POST"&gt;
  &lt;input type="hidden" name="__method" value="DELETE" /&gt;
&lt;/form&gt;
```

Note::

The HTTP request method can only be changed for POST requests

Change-Id: Ibe753ca4bfcc3dc5b579e39fd13af95b79bc1f83

Resolves: #47137

Releases: master, 2.0

History

#1 - 2013-04-11 19:44 - Gerrit Code Review

- Status changed from Accepted to Under Review

Patch set 1 for branch **master** has been pushed to the review server.

It is available at <https://review.typo3.org/19800>

#2 - 2013-04-12 18:34 - Gerrit Code Review

Patch set 2 for branch **master** has been pushed to the review server.

It is available at <https://review.typo3.org/19800>

#3 - 2013-04-12 18:42 - Gerrit Code Review

Patch set 3 for branch **master** has been pushed to the review server.

It is available at <https://review.typo3.org/19800>

#4 - 2013-04-17 17:07 - Gerrit Code Review

Patch set 1 for branch **2.0** has been pushed to the review server.

It is available at <https://review.typo3.org/20014>

#5 - 2013-04-17 17:36 - Bastian Waidelich

- *Status changed from Under Review to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset commit:f5b5024bdb618b5b018188ea16bd138490a02b1c.