

TYPO3.Surf - Bug # 48135

Status:	Resolved	Priority:	Must have
Author:	Dietrich Heise	Category:	
Created:	2013-05-13	Assigned To:	Dietrich Heise
Updated:	2013-08-22	Due date:	
Subject:	funtion prepareCommand() in class ShellCommandService		
Description			
<p>If the command-array is imploded by a semicolon only the return code of the last command is used for the exit code.</p> <p>Example: a TYPO3.Surf TASK - execute function:</p> <pre>\$commands = array("/bin/false", "ls la"); \$this->shell->executeOrSimulate(\$commands, \$node, \$deployment);</pre> <p>This example will have an exit code of zero!</p> <p>For this example it is better to implode the commands by "&&", so if one command fail, no other command will be executed and the exit code ist right.</p> <pre>--- a/Classes/TYPO3/Surf/Domain/Service/ShellCommandService.php +++ b/Classes/TYPO3/Surf/Domain/Service/ShellCommandService.php @ -188,7 +188,7 @ class ShellCommandService { if (is_string(\$command)) { return trim(\$command); } elseif (is_array(\$command)) { - return implode(':', \$command); + return implode('&&', \$command); } else { throw new \TYPO3\Surf\Exception\TaskExecutionException('Command must be string or array, ' . gettype(\$command) . ' given.', 1312454 } }</pre>			

Associated revisions

Revision f543edc4 - 2013-08-22 13:30 - Dietrich Heise

[BUGFIX] Return code of multiple shell commands

Additionally adds a unit test for shell process execution and refactors some duplicate code.

Resolves: #48135

Change-Id: I15bf9cb51bf5ea40d618cce860886c5cae2cba51

History

#1 - 2013-05-13 14:00 - Dietrich Heise

```
$commands = array(
    "/bin/false",
    "ls -la"
);
$this->shell->executeOrSimulate($commands, $node, $deployment);
```

```
--- a/Classes/TYPO3/Surf/Domain/Service/ShellCommandService.php
+++ b/Classes/TYPO3/Surf/Domain/Service/ShellCommandService.php
@@ -188,7 +188,7 @@ class ShellCommandService {
    if (is_string($command)) {
        return trim($command);
    } elseif (is_array($command)) {
-       return implode(':', $command);
+       return implode('&&', $command);
    } else {
        throw new \TYPO3\Surf\Exception\TaskExecutionException('Command must be string or array, ' . gettype($command) . '
given.', 1312454
    }
}
```

#2 - 2013-08-01 17:05 - Tobias Liebig

- Status changed from New to Needs Feedback
- Assigned To set to Dietrich Heise

Could you please make a change in Gerrit for this?

#3 - 2013-08-02 20:41 - Gerrit Code Review

Patch set 1 for branch **master** has been pushed to the review server.
It is available at <https://review.typo3.org/22776>

#4 - 2013-08-02 20:42 - Dietrich Heise

ready for review
<https://review.typo3.org/22776>

#5 - 2013-08-22 13:30 - Gerrit Code Review

Patch set 2 for branch **master** has been pushed to the review server.
It is available at <https://review.typo3.org/22776>

#6 - 2013-08-22 15:30 - Dietrich Heise

- Status changed from Needs Feedback to Resolved
- % Done changed from 0 to 100

Applied in changeset commit:f543edc4485107037ed0e81ee4aef48b71f1bfc0.