

TCA Reference - Feature # 49716

Status:	Closed	Priority:	Must have
Author:	Markus Klein	Category:	
Created:	2013-07-05	Assigned To:	Francois Suter
Updated:	2014-08-01	Due date:	
Subject:	label_func addition for rendering IRRE headers		
Description			
<p>The new TCA option 'label_userFunc_options' allows to pass additional information to the label_userFunc.</p> <p>Example:</p> <pre>'ctrl' => array('title' => 'LLL:EXT:lang/locallang_tca.xlf:theTable', 'label' => 'uid', 'label_userFunc' => 'UserFunc.php:UserFunc->getInlineLabel', 'label_userFunc_options' => array('special' => array('this', 'that')))</pre>			
<p>The getInlineLabel() can set the title as follows:</p> <pre>public function getInlineLabel(array &\$params) { \$fields = isset(\$params['options']['special']) && is_array(\$params['options']['special']) ? \$params['options']['special'] : array(); \$title = array(); foreach (\$fields as \$f) { \$title[] = \$params['row'][\$f]; } \$params['title'] = '<dl>' . implode("", \$title) . '</dl>'; }</pre>			
Related issues:			
related to TYPO3 CMS Usability Team - Suggestion # 36052: Visual improvements...		Resolved	
related to Core - Bug # 51411: Label user function for sys_file_reference use...		Resolved	2013-08-27
related to Core - Feature # 49721: Add label_userFunc_options to BackendUtility		Resolved	2013-07-06

Associated revisions

Revision 0386ee6b - 2014-02-19 20:13 - Francois Suter

[FEATURE] Document formattedLabel_userFunc

Two new properties were added to the "ctrl" section of the TCA,

formattedLabel_userFunc and formattedLabel_userFunc_options.

Resolves: #49716

Releases: 6.2

Change-Id: Iab01736200c082d1e0b2ca7e61a37f9143fa8a8e

Reviewed-on: <https://review.typo3.org/27732>

Reviewed-by: Francois Suter

Tested-by: Francois Suter

History

#1 - 2013-07-05 21:17 - Markus Klein

Change: <https://review.typo3.org/21916>

#2 - 2013-09-01 13:47 - Philipp Gampe

The corresponding change needed a follow up, because the label must not contain markup.

Thus for IRRE headers, there is a new configuration option `inlineLabel_userFunc` with the same signature as the known `label_userFunc`. This new config option is preferred over the normal label user function.

The additional behavior with the `label_userFunc_options` is preserved, although it is not used for FAL IRRE fields.

#3 - 2013-09-17 17:34 - Ernesto Baschny

Please note that the follow-up is not finished / reviewed (#51411) yet, so this is not in the core. But this has to be fixed because the current behaviour breaks some backend elements (Workspaces, Sys-log..)

#4 - 2013-09-24 09:02 - Markus Klein

The follow-up is merged now. The new label option is called "formattedLabel_userFunc". The user can provide a function that returns a HTML formatted label for a row. As of 6.2 this is only used for displaying IRRE inline element headers.

#5 - 2014-02-19 20:12 - Gerrit Code Review

- Status changed from New to Under Review

Patch set 1 for branch **master** of project **Documentation/TYPO3/Reference/Tca** has been pushed to the review server.

It is available at <https://review.typo3.org/27732>

#6 - 2014-02-19 20:13 - Francois Suter

- Assigned To set to Francois Suter

#7 - 2014-02-19 20:35 - Francois Suter

- Status changed from Under Review to Resolved

- % Done changed from 0 to 100

Applied in changeset commit:0386ee6b4b26305dae4276f4f3db1cdb1d211634.

#8 - 2014-08-01 14:22 - Francois Suter

- *Status changed from Resolved to Closed*