

## Core - Bug # 53368

|  |   |                     |                   |
|--|---|---------------------|-------------------|
| <b>Status:</b>   | Resolved  | <b>Priority:</b>    | Must have         |
| <b>Author:</b>   | Jo Hasenau                                      | <b>Category:</b>    | Performance       |
| <b>Created:</b>  | 2013-11-06                                      | <b>Assigned To:</b> |                   |
| <b>Updated:</b>  | 2013-11-08                                      | <b>Due date:</b>    |                   |
| <b>TYPO3 Version:</b>  | 6.2   |                     |                   |
| <b>PHP Version:</b>  | 5.4   |                     |                   |
| <b>Complexity:</b>   |   |                     |                   |
| <b>Is Regression:</b>  | No  |                     |                   |
| <b>Sprint Focus:</b>   |   |                     |                   |
| <b>Subject:</b>  | Use getPagesTSconfig(\$tscPID) only once per ID |                     |                   |
| <b>Description</b>   |   |                     |                   |
| <p>PageLayoutView::isRTEforField is called on every record that is displayed in a Web&gt;Page. And this will call BackendUtility::getPagesTSconfig(\$tscPID) every time once and again, and thus parsing the PageTS over and over on the same hit. If you have 50 content elements on a page, this can get very expensive.</p> <p>Solution: Create a variable that stores the RTEsetup for a particular ID</p> |   |                     |                   |
| <b>Related issues:</b>   |   |                     |                   |
| related to Core - Bug # 53370: Cache getPagesTSconfig per ID and rootline  |   | <b>Resolved</b>     | <b>2013-11-06</b> |
| related to Core - Task # 53462: Add cache to getPagesTSconfig()  |   | <b>Resolved</b>     | <b>2013-11-08</b> |

### Associated revisions

**Revision c9cd9c40 - 2013-11-08 16:50 - Jo Hasenau**

[BUGFIX] Use getPagesTSconfig(\$tscPID) only once per ID

PageLayoutView::isRTEforField is called on every record that is displayed in a Web>Page. And this will call BackendUtility::getPagesTSconfig(\$tscPID) every time once and again, and thus parsing the PageTS over and over on the same hit. If you have 50 content elements on a page, this can get very expensive.

Solution: Create a variable that stores the RTEsetup for a particular ID

Resolves: #53368

Releases: 6.2

Change-Id: I7efcefb0c12c856e9417ca8bb655acaabd4f15cc

Reviewed-on: <https://review.typo3.org/25181>

Reviewed-by: Oliver Klee

Reviewed-by: Jo Hasenau

Reviewed-by: Alexander Opitz

Tested-by: Alexander Opitz

Reviewed-by: Sebastian Fischer

Reviewed-by: Wouter Wolters

Reviewed-by: Peter Foerger

Tested-by: Peter Foerger  
Tested-by: Philipp Gampe  
Reviewed-by: Philipp Gampe  
Reviewed-by: Stefan Neufeind  
Tested-by: Stefan Neufeind

## History

---

### #1 - 2013-11-06 12:17 - Gerrit Code Review

- *Status changed from New to Under Review*

Patch set 4 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.  
It is available at <https://review.typo3.org/25181>

### #2 - 2013-11-06 12:49 - Gerrit Code Review

Patch set 5 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.  
It is available at <https://review.typo3.org/25181>

### #3 - 2013-11-08 17:30 - Jo Hasenau

- *Status changed from Under Review to Resolved*  
- *% Done changed from 0 to 100*

Applied in changeset commit:c9cd9c40ef9e24cf179c172489508987f050ea02.