

TYPO3.Fluid - Bug # 55142

Status:	Resolved	Priority:	Should have
Author:	Alexander Stehlik	Category:	Widgets
Created:	2014-01-19	Assigned To:	
Updated:	2014-01-21	Due date:	
Has patch:	No		
Affected Flow version:	Git master		
Subject:	Use getPropertyPath in autocomplete widget		
Description	<p>Currently the AutocompleteController uses ObjectAccess::getProperty() for retrieving the property that was searched for in the query.</p> <p>The query is currently flexible enough to support sub-properties to be searched. An example: if you have a User object you could configure an autocomplete widget that searches for name.fullName. The query will execute that search without problems and find the users.</p> <p>But as soon as the results are build the widget crashes because it can not access the property.</p> <p>A simple fix that should not cause any side effects would be to use ObjectAccess::getPropertyPath() instead.</p>		

Associated revisions

Revision 5332635e - 2014-01-19 16:38 - Alexander Stehlik

[BUGFIX] Use getPropertyPath in autocomplete widget

Since the query in the widget that searches for autocomplete items already supports nested properties the building of the result array now also uses ObjectAccess::getPropertyPath() instead of ObjectAccess::getProperty().

Resolves: #55142

Releases: master

Change-Id: I6781767e926b45ef2d92e37eeab889974a0d14b7

History

#1 - 2014-01-19 16:38 - Gerrit Code Review

- Status changed from New to Under Review

Patch set 1 for branch **master** of project **Packages/TYPO3.Fluid** has been pushed to the review server.

It is available at <https://review.typo3.org/26931>

#2 - 2014-01-21 13:36 - Alexander Stehlik

- Status changed from Under Review to Resolved

- % Done changed from 0 to 100

Applied in changeset commit:5332635efb2b7f02a69ed87026edfd80fd42b040.

