

Core - Bug # 56701

Status:	Closed	Priority:	Must have
Author:	Jost Baron	Category:	TypoScript
Created:	2014-03-10	Assigned To:	
Updated:	2015-01-24	Due date:	
TYPO3 Version:	6.2		
PHP Version:			
Complexity:			
Is Regression:	No		
Sprint Focus:			
Subject:	Static template of css_styled_content can no longer be included using <INCLUDE_TYPOSCRIPT>		
Description			
<p>If it is included using an <INCLUDE> directive, certain other TS (Plugin rendering definitions) is not included. The problematic commit is 3ce53655a3739dadd732556e1902e7686ef59260 (https://review.typo3.org/#/c/27587/).</p> <p>Steps to reproduce:</p> <ol style="list-style-type: none">1. Create a new TYPO3 installation using the current master branch.2. Install the development branch of EXT:flux (https://github.com/FluidTYPO3/flux)3. Install the development branch of EXT:fluidcontent (https://github.com/FluidTYPO3/fluidcontent) <p>Create a new root page with the following root template:</p> <p>Constants:</p> <pre><INCLUDE_TYPOSCRIPT: source="FILE:EXT:css_styled_content/static/constants.txt"></pre> <p>Setup:</p> <pre><INCLUDE_TYPOSCRIPT: source="FILE:EXT:css_styled_content/static/setup.txt"> page = PAGE page.10 < styles.content.get</pre> <ol style="list-style-type: none">4. Check out commit 3ce53655a3739dadd732556e1902e7686ef59260 of the TYPO3 core and view the full Typoscript Template in the Analyzer. There is no object tt_content.fluidcontent_content being defined.5. When using the previous commit 85d88e4f9d0efe4443bace89ce98c585255cacfd, tt_content.fluidcontent_content is defined correctly.			
Related issues:			
duplicates Core - Bug # 56570: No rendering definition for CE / no list for p...		Closed	2014-03-05

History

#1 - 2014-03-10 12:07 - Jan Kiesewetter

I also reported it here: <http://forge.typo3.org/issues/56570>

#2 - 2014-03-10 12:20 - Jan Kiesewetter

Thanks for pointing me to the commit!

It seems to work if you add

```
// Mark the delivered TypoScript templates as "content rendering template" (providing the hooks of "static template 43" = content (default))
$GLOBALS['TYPO3_CONF_VARS']['FE']['contentRenderingTemplates'][] = 'yourpackagekey/Configuration/TypoScript';
```

to ext_localconf.php

#3 - 2014-03-18 09:46 - André Wuttig

I try to get it work for our TYPO3 6.2 application. Can anyone describe a best practice how to include TS (Plugin rendering definitions) correctly?!

#4 - 2014-03-18 15:27 - Jan Kieseewetter

If your template is within an extension you can do it like this:

<https://bitbucket.org/t3see/basepackage/commits/2df60c989b1f228db2bca8deac3a748564e7bcd8>

#5 - 2015-01-24 22:16 - Mathias Schreiber

- Status changed from New to Closed

dupe

#6 - 2015-01-24 22:17 - Mathias Schreiber

- Status changed from Closed to New

- Target version changed from 6.2.0 to 7.2 (Frontend)

#7 - 2015-01-24 22:19 - Mathias Schreiber

- Status changed from New to Closed

closed. works like a charm