

TypoScript Reference (TSref) - Feature # 57171

Status:	Resolved	Priority:	Should have
Author:	Oliver Hader	Category:	
Created:	2014-03-22	Assigned To:	Chris topher
Updated:	2014-03-25	Due date:	

Subject: select: Enable queries using "root" and "-1" for pidInList

Description

The change refers to <http://docs.typo3.org/typo3cms/TyposcriptReference/Functions/Select/Index.html>

select.pidInList now supports the new values "root" and "-1".

Add to documentation

Since TYPO3 CMS 6.2 it is possible to select records from the root-page level, like from the table "sys_category". For this case, it is required that "root" is set.

Besides that, version records can be selected directly by setting the value to "-1", this allows to directly select workspace versioned records.

Special keyword: "this" is replaced with the id of the current page, "root" is replaced with the root-page level (records with pid=0)

Example:

```
// Fetching related sys_category records
// stored in the MM intermediate table
10 = CONTENT
10 {
    table = sys_category
    select {
        pidInList = root,-1
        selectFields = sys_category.*
        join = sys_category_record_mm ON sys_category_record_mm.uid_local = sys_category.uid
        where.data = field:_ORIG_uid // field:uid
        where.intval = 1
        where.wrap = sys_category_record_mm.uid_foreign=|
        orderBy = sys_category_record_mm.sorting_foreign
        languageField = sys_category.sys_language_uid
    }
}
```

See #57168

Related issues:

related to Core - Task # 57168: Enable queries using "root" and "-1" for pidInList...

Resolved

2014-03-21

Associated revisions

Revision b246b59b - 2014-03-25 12:02 - Chris topher

[TASK] select: Enable queries using "root" and "-1" for pidInList

Property select.pidInList of the select function now supports the new values "root" and "-1". Document them!

Change-Id: I923b381ac0ea7a75d806c1f532f4b994b86e08fc

Resolves: #57171

Reviewed-on: <https://review.typo3.org/28752>

Reviewed-by: Chris topher

Tested-by: Chris topher

History

#1 - 2014-03-22 02:04 - Oliver Hader

The feature got merged in between.

#2 - 2014-03-25 11:57 - Chris topher

- *Assigned To set to Chris topher*

#3 - 2014-03-25 11:58 - Chris topher

- *Subject changed from Enable queries using "root" and "-1" for pidInList to select: Enable queries using "root" and "-1" for pidInList*

#4 - 2014-03-25 11:58 - Gerrit Code Review

- *Status changed from New to Under Review*

Patch set 1 for branch **master** of project **Documentation/TYPO3/Reference/Typoscript** has been pushed to the review server.

It is available at <https://review.typo3.org/28752>

#5 - 2014-03-25 12:00 - Gerrit Code Review

Patch set 2 for branch **master** of project **Documentation/TYPO3/Reference/Typoscript** has been pushed to the review server.

It is available at <https://review.typo3.org/28752>

#6 - 2014-03-25 12:00 - Gerrit Code Review

Patch set 3 for branch **master** of project **Documentation/TYPO3/Reference/Typoscript** has been pushed to the review server.

It is available at <https://review.typo3.org/28752>

#7 - 2014-03-25 13:47 - Chris topher

- *Status changed from Under Review to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset commit:b246b59b0462ad8d3545a0f49d233f72992ac565.