

Base Distribution - Task # 57822

Status:	Resolved	Priority:	Should have
Author:	Carsten Bleicker	Category:	
Created:	2014-04-11	Assigned To:	
Updated:	2014-04-11	Due date:	
Subject:	Enabled content cache and uncached prototype throwing exception		
Description			
<pre>prototype(PIPEU.Site:SimpleBasket) < prototype(TYPO3.TypoScript:Template) prototype(PIPEU.Site:SimpleBasket) { templatePath = 'resource://PIPEU.Site/Private/Templates/TypoScriptObjects/SimpleBasket.html' partialRootPath = 'resource://PIPEU.Site/Private/Partials' basketNode = \${q(site).find('basket').get(0)} @cache { mode = 'uncached' context { 1 = 'documentNode' } } }</pre>			
its used like this:			
<pre>page{ parts{ simpleBasket = PIPEU.Site:SimpleBasket } }</pre>			
Exception:			
Uncaught exception #1332491864 in line 195 of /Users/pumatertion/Sites/neos.pipeu/Data/Temporary/Development/Cache/Code/Flow_Object_Classes/TYPO3_Eel_FlowQuery_FlowQuery.p Query.php: No operation which satisfies the runtime constraints found for "find".			

History

#1 - 2014-04-11 11:55 - Carsten Bleicker

Sorry, missing pre tag for codesnippets :(

```
prototype(PIPEU.Site:SimpleBasket) < prototype(TYPO3.TypoScript:Template)
prototype(PIPEU.Site:SimpleBasket) {
  templatePath = 'resource://PIPEU.Site/Private/Templates/TypoScriptObjects/SimpleBasket.html'
  partialRootPath = 'resource://PIPEU.Site/Private/Partials'
  basketNode = ${q(site).find('basket').get(0)}

  @cache {
    mode = 'uncached'
    context {
      1 = 'documentNode'
    }
  }
}
```

```

}

page{
  parts{
    simpleBasket = PIPEU.Site:SimpleBasket
  }
}

```

#2 - 2014-04-11 12:35 - Carsten Bleicker

You can close this ticket.

Its solved with this settings:

```

prototype(PIPEU.Site:SimpleBasket) < prototype(TYPO3.TypoScript:Template)
prototype(PIPEU.Site:SimpleBasket) {
  templatePath = 'resource://PIPEU.Site/Private/Templates/TypoScriptObjects/SimpleBasket.html'
  partialRootPath = 'resource://PIPEU.Site/Private/Partials'
  basketNode = ${q(site).find('basket').get(0)}

  @cache {
    mode = 'uncached'
    context {
      1 = 'site'
      2 = 'documentNode'
    }
  }
}

```

#3 - 2014-04-11 12:39 - Christian Müller

- Status changed from New to Resolved

The "context" configuration inside @cache needs to contain all context variables that are needed to render this TypoScript object. "site" is used but was not included.

#4 - 2014-04-11 12:45 - Carsten Bleicker

Just to be sure,

i have to make sure by myself wich context variables also the inherited by extending another prototype?

maybe a wired example but in theory:

```

prototype(MY:FOO) < prototype(TYPO3.Neos:Breadcrumb)
prototype(MY:FOO){

  @cache {
    mode = 'uncached'

```

```
context {  
  # This one because its used in the Breadcrumb?  
  1 = 'node'  
}  
}  
}
```