

## Core - Bug # 58288

<b>Status:</b>	Resolved	<b>Priority:</b>	Must have
<b>Author:</b>	Helmut Hummel	<b>Category:</b>	
<b>Created:</b>	2014-04-28	<b>Assigned To:</b>	
<b>Updated:</b>	2014-07-10	<b>Due date:</b>	
<b>TYPO3 Version:</b>	6.2		
<b>PHP Version:</b>			
<b>Complexity:</b>			
<b>Is Regression:</b>	No		
<b>Sprint Focus:</b>			
<b>Subject:</b>	Cache that write absolute paths needs PATH_site in cache identifier		
<b>Description</b>			
<p>The package cache writes paths to extension directories (TYPO3_LOADED_EXT) into the cache.</p> <p>When calling e.g. a TYPO3 cli script from a different directory (due to different mounts) and this cache does not exist yet, it will be written with absolute paths taken from PATH_site of the cli</p> <p>When then calling the website, many things will fail as relative path calculations are done with the current PATH_site</p> <p>The easiest way to tackle this issue, is to make the caches depend on PATH_site, like it is for ext_tables and ext_localconf caches</p>			
<b>Related issues:</b>			
related to Core - Bug # 60737: Symlinks as Document roots are breaking the cache		<b>Resolved</b>	<b>2014-08-01</b>
duplicated by Core - Bug # 59088: PathUtility::stripPathSitePrefix() fails wi...		<b>Closed</b>	<b>2014-05-24</b>
duplicated by Core - Bug # 58952: Inconsistent extension/package relative paths		<b>Closed</b>	<b>2014-05-20</b>
duplicated by Core - Bug # 60224: Package Paths should be relative to TYPO3_site		<b>Closed</b>	<b>2014-07-10</b>

### Associated revisions

**Revision d3c95a1c - 2014-07-10 22:56 - Helmut Hummel**

[BUGFIX] Use PATH\_site in cache identifier for package cache

The package cache writes paths to extension directories (TYPO3\_LOADED\_EXT) into the cache.

This will result in wrong caches when the same TYPO3 instance is called from a different absolute directory e.g. from a different mount or symlink.

To avoid this, the cache identifier now includes PATH\_site which is the current absolute path of the TYPO3 instance.

Additionally we now only include the modification time of the package states file instead of the md5 of the complete content into account, which should be much faster and also enough.

Resolves: #58288

Releases: 6.2, 6.3

Change-Id: I7c8de41c608beab282f2b8bbeab39f257a9a6a6f

Reviewed-on: <https://review.typo3.org/31565>

Reviewed-by: Markus Klein

Tested-by: Markus Klein

Reviewed-by: Stefan Neufeind

Tested-by: Stefan Neufeind

## Revision 9f6150fa - 2014-07-13 22:28 - Helmut Hummel

[BUGFIX] Use PATH\_site in cache identifier for package cache

The package cache writes paths to extension directories (TYPO3\_LOADED\_EXT) into the cache.

This will result in wrong caches when the same TYPO3 instance is called from a different absolute directory e.g. from a different mount or symlink.

To avoid this, the cache identifier now includes PATH\_site which is the current absolute path of the TYPO3 instance.

Additionally we now only include the modification time of the package states file instead of the md5 of the complete content into account, which should be much faster and also enough.

Resolves: #58288

Releases: 6.2, 6.3

Change-Id: I7c8de41c608beab282f2b8bbeab39f257a9a6a6f

Reviewed-on: <https://review.typo3.org/31580>

Reviewed-by: Stefan Neufeind <[typo3.neufeind@speedpartner.de](mailto:typo3.neufeind@speedpartner.de)>

Tested-by: Stefan Neufeind <[typo3.neufeind@speedpartner.de](mailto:typo3.neufeind@speedpartner.de)>

## History

---

### #1 - 2014-06-03 23:27 - Stefano Kowalke

I encounter the same issue. A possible reason might be a two disk setup. I have a SSD with the OS and a HDD with my \$HOME folder, where the \$HOME folder on the SSD is just a symlink to the one on the HDD.

```
$ ll /Users
```

```
lrwxr-xr-x  1 root    admin   23B 15 Jul 2013 sok -> /Volumes/HDD/Users/sok/
```

So while PATH\_site get filled with /Volumes/HDD/Users/Sites/TYPO3/www.introduction.dev, all other functions determine this path /Users/sok/Sites/TYPO3/www.introduction.dev/.

### #2 - 2014-07-10 18:10 - Gerrit Code Review

- Status changed from Accepted to Under Review

Patch set 1 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.  
It is available at <https://review.typo3.org/31565>

#### **#3 - 2014-07-10 18:17 - Gerrit Code Review**

Patch set 2 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.  
It is available at <https://review.typo3.org/31565>

#### **#4 - 2014-07-10 18:34 - Gerrit Code Review**

Patch set 3 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.  
It is available at <https://review.typo3.org/31565>

#### **#5 - 2014-07-10 20:16 - Gerrit Code Review**

Patch set 4 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.  
It is available at <https://review.typo3.org/31565>

#### **#6 - 2014-07-10 22:56 - Gerrit Code Review**

Patch set 1 for branch **TYPO3\_6-2** of project **Packages/TYPO3.CMS** has been pushed to the review server.  
It is available at <https://review.typo3.org/31580>

#### **#7 - 2014-07-10 23:30 - Helmut Hummel**

- *Status changed from Under Review to Resolved*
- *% Done changed from 0 to 100*

Applied in changeset commit:d3c95a1cd42922d304246b03001347e099895166.