

TYPO3.Surf - Bug # 59420

Status:	New	Priority:	Should have
Author:	Andreas Dörler	Category:	
Created:	2014-06-09	Assigned To:	
Updated:	2014-06-09	Due date:	

Subject: Make \$localPackagePath configurable in RsyncTask

Description

Hi,

currently **\$localPackagePath** is hardcoded to

```
$localPackagePath = $deployment->getWorkspacePath($application);
```

and the **workspacePath** is not configurable as far as I've seen:

```
/**
 * Get a local workspace directory for the application
 */
public function getWorkspacePath(Application $application) {
    return FLOW_PATH_DATA . 'Surf' . $this->getName() . '/' . $application->getName();
}
```

If one uses Jenkins for deployment, the source will be checked out from GIT by Jenkins itself, so there is no need to do it again in SURF.

Currently we use the following workaround:

```
$application->setOption('transferMethod', NULL); // disable rsync
$application->setOption('packageMethod', NULL); // disable SURF git checkout - we use jenkins git checkout
$application->setOption('customrsync', array('customLocalPackagePath',
'/var/lib/jenkins/workspace/'.$application->getName()));
$workflow->addTask('typo3.surf:transfer:customrsync', 'transfer', $application);
```

In a copy of the default RsyncTask we use the given option if set:

```
$localPackagePath = (isset($options['customrsync']['customLocalPackagePath'])) ?
$options['customrsync']['customLocalPackagePath'] : $deployment->getWorkspacePath($application);
```

It would be great to have this option included in TYPO3.Surf.

Kind regards
Andreas

History