

Core - Bug # 63778

Bug # 63692 (Accepted): Memory consumption while bulk inserting

Status:	Resolved	Priority:	Should have
Author:	Stephan Großberndt	Category:	Performance
Created:	2014-12-11	Assigned To:	
Updated:	2014-12-11	Due date:	
TYPO3 Version:	6.2		
PHP Version:			
Complexity:	no-brainer		
Is Regression:	No		
Sprint Focus:			
Subject:	Do not fetch TSconfig in DataHandler->process_datamap for non-page-records		
Description			
<p>In DataHandler->process_datamap for each record DataHandler->getTCMAIN_TSconfig is executed, but the TSconfig is used only if \$status 'new' && \$table 'pages'</p> <pre>if (\$recordAccess) { // Here the "pid" is set IF NOT the old pid was a string pointing to a place in the subst-id array. list(\$tscPID) = BackendUtility::getTSCpid(\$table, \$id, \$old_pid_value ? \$old_pid_value : \$fieldArray['pid']); \$TSConfig = \$this->getTCMAIN_TSconfig(\$tscPID); if (\$status == 'new' && \$table == 'pages' && is_array(\$TSConfig['permissions.'])) { \$fieldArray = \$this->setTSconfigPermissions(\$fieldArray, \$TSConfig['permissions.']); } }</pre>			

Associated revisions

Revision 68806a35 - 2014-12-11 21:37 - Stephan Großberndt

[BUGFIX] Do not fetch TSconfig in process_datamap for non-page-records

In DataHandler->process_datamap for each record getTCMAIN_TSconfig() is executed, but the returned TSconfig is used only if table is "pages" and status is "new".

Fetches the TSconfig only if table is "pages" and status is "new".

Resolves: #63778

Releases: master, 6.2

Change-Id: Ifded6daf2b5b6b61a9c95ba3962566450a07d72e

Reviewed-on: <http://review.typo3.org/35304>

Reviewed-by: Markus Klein <klein.t3@reelworx.at>

Tested-by: Markus Klein <klein.t3@reelworx.at>

Reviewed-by: Lukas Krieger <lukas.krieger@me.com>

Reviewed-by: Wouter Wolters <typo3@wouterwolters.nl>

Tested-by: Wouter Wolters <typo3@wouterwolters.nl>

Revision 3a19c861 - 2014-12-11 22:01 - Stephan Großberndt

[BUGFIX] Do not fetch TSconfig in process_datamap for non-page-records

In DataHandler->process_datamap for each record getTCEMAIN_TSconfig()
is executed, but the returned TSconfig is used only if table is "pages"
and status is "new".

Fetches the TSconfig only if table is "pages" and status is "new".

Resolves: #63778

Releases: master, 6.2

Change-Id: Ifded6daf2b5b6b61a9c95ba3962566450a07d72e

Reviewed-on: <http://review.typo3.org/35318>

Reviewed-by: Wouter Wolters <typo3@wouterwolters.nl>

Tested-by: Wouter Wolters <typo3@wouterwolters.nl>

History

#1 - 2014-12-11 15:04 - Alexander Opitz

- Parent task set to #63692

#2 - 2014-12-11 15:32 - Gerrit Code Review

- Status changed from New to Under Review

Patch set 1 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.

It is available at <http://review.typo3.org/35304>

#3 - 2014-12-11 15:58 - Gerrit Code Review

Patch set 2 for branch **master** of project **Packages/TYPO3.CMS** has been pushed to the review server.

It is available at <http://review.typo3.org/35304>

#4 - 2014-12-11 21:37 - Gerrit Code Review

Patch set 1 for branch **TYPO3_6-2** of project **Packages/TYPO3.CMS** has been pushed to the review server.

It is available at <http://review.typo3.org/35318>

#5 - 2014-12-11 22:00 - Stephan Großberndt

- Status changed from Under Review to Resolved

- % Done changed from 0 to 100

Applied in changeset commit:68806a3583e34395cc7b2a1ae525ce49c00ce2a0.