Status: Resolved **Priority:** Should have Author: Peter Niederlag Category: File Abstraction Layer (FAL) Created: 2015-01-09 Assigned To:

2015-01-29 Due date: **Updated:**

TYPO3 Version: 6.2

PHP Version: Complexity:

Is Regression: No

Sprint Focus: On Location Sprint

Subject: GIFBUILDER with FAL and UTF-8 filesystem

Description

given is a file "wärme.png"

given is the file is used in a content element via a file refernce (FAL) given is a TypoScript setup to render the image via a GIFBUILDER Object

then I see a broken image rendered as the filename is not processed correctly

ContentObjectRender->getImgResource() does return '\$processedFileObject->getPublicUrl()' inside the imgResource of the processdFile which is rawurlencoded().

This patch/change cures the problem by adding an extra rawurldecod() inside the GifBuilder. Does not feel like the proper solution and I will see if it breaks anywhere else for some time.

iff --git a/typo3/sysext/frontend/Classes/Imaging/GifBuilder.php b/typo3/sysext/frontend/Classes/Imaging/GifBuilder.php index 9d13e6c..306b676 100644

--- a/typo3/sysext/frontend/Classes/Imaging/GifBuilder.php

+++ b/typo3/sysext/frontend/Classes/Imaging/GifBuilder.php

@@ -206,7 +206,7 @@ class GifBuilder extends \TYPO3\CMS\Core\Imaging\GraphicalFunctions {

\$fileInfo = \$this->getResource(\$conf['file'], \$conf['file.']);

if (\$fileInfo) {

 $\frac{(')}{[[alnum:]]+$/', ", basename($fileInfo[3]))};$

\$this->setup[\$theKey . '.']['file'] = \$fileInfo[3];

\$this->setup[\$theKey . '.']['file'] = rawurldecode(\$fileInfo[3]);

\$this->setup[\$theKey . '.']['BBOX'] = \$fileInfo;

\$this->objBB[\$theKey] = \$fileInfo;

if (\$conf['mask']) {

Related issues:

related to Core - Bug # 65378: Scaling/cropping images in GIFBUILDER does not... Resolved 2015-02-27 related to Core - Bug # 67192: Problem with IMAGE object when image file name... New 2015-05-29

Associated revisions

Revision fd232ede - 2015-01-29 08:24 - Torben Hansen

[BUGFIX] Use getForLocalProcessing() for FAL images in GIFBUILDER

GIFBUILDER must use getForLocalProcessing() for FAL images, so

2015-08-04 1/5 image processing is possible for files containing special chars (e.g. umlauts) when using an UTF-8 filesystem.

Resolves: #64224 Releases: master, 6.2

Change-Id: lb3b372ceea1afa839787c61a3f118b3f62f05dcc

Reviewed-on: http://review.typo3.org/36180

Reviewed-by: Frans Saris < franssaris@gmail.com>
Reviewed-by: Benjamin Mack < benni@typo3.org>
Tested-by: Benjamin Mack < benni@typo3.org>

Revision cbdbacc7 - 2015-01-29 08:25 - Torben Hansen

[BUGFIX] Use getForLocalProcessing() for FAL images in GIFBUILDER

GIFBUILDER must use getForLocalProcessing() for FAL images, so image processing is possible for files containing special chars (e.g. umlauts) when using an UTF-8 filesystem.

Resolves: #64224 Releases: master, 6.2

Change-Id: lb3b372ceea1afa839787c61a3f118b3f62f05dcc

Reviewed-on: http://review.typo3.org/36180

Reviewed-by: Frans Saris <franssaris@gmail.com>
Tested-by: Frans Saris <franssaris@gmail.com>
Reviewed-by: Benjamin Mack <benni@typo3.org>
Tested-by: Benjamin Mack <benni@typo3.org>

(cherry picked from commit fd232edeab2c72a7bac582b454b8db6b788f017c)

Reviewed-on: http://review.typo3.org/36340

Revision ef5f6cc8 - 2015-03-04 19:26 - Torben Hansen

[BUGFIX] Regression when scaling/cropping in GIFBUILDER

The fix for issue #64224 introduced a regression in GIFBUILDER resulting in problems with image scaling/cropping.

For \$fileInfo and \$maskInfo: use 'processedFile' for FAL files if available and correctly distinguish between FAL- and non-FAL files otherwise by checking for 'origFile'.

Resolves: #65378 Related: #64224 Releases: master, 6.2

Change-Id: lb472bdcdc7f814e50ebd18e084f5fbe7d09fc410

Reviewed-on: http://review.typo3.org/37483

Reviewed-by: Stephan Großberndt < stephan@grossberndt.de > Tested-by: Stephan Großberndt < stephan@grossberndt.de >

Reviewed-by: Frans Saris <franssaris@gmail.com>
Tested-by: Stefan Froemken froemken@gmail.com>

2015-08-04 2/5

Tested-by: Christoph Lehmann < christoph.lehmann@networkteam.com>

Tested-by: Philipp Mueller cphilipp.mueller@lavitto.ch>
Reviewed-by: Christian Kuhn clolli@schwarzbu.ch>
Tested-by: Christian Kuhn clolli@schwarzbu.ch>

Revision 835be9a8 - 2015-03-04 19:27 - Torben Hansen

[BUGFIX] Regression when scaling/cropping in GIFBUILDER

The fix for issue #64224 introduced a regression in GIFBUILDER resulting in problems with image scaling/cropping.

For \$fileInfo and \$maskInfo: use 'processedFile' for FAL files if available and correctly distinguish between FAL- and non-FAL files otherwise by checking for 'origFile'.

Resolves: #65378 Related: #64224 Releases: master, 6.2

Change-Id: lb472bdcdc7f814e50ebd18e084f5fbe7d09fc410

Reviewed-on: http://review.typo3.org/37533

Reviewed-by: Christian Kuhn < lolli@schwarzbu.ch>
Tested-by: Christian Kuhn < lolli@schwarzbu.ch>

History

#1 - 2015-01-09 20:36 - Peter Niederlag

- Subject changed from GIFBUILDE with FAL and UTF-8 filesystem to GIFBUILDER with FAL and UTF-8 filesystem

#2 - 2015-01-09 20:36 - Peter Niederlag

- Category set to File Abstraction Layer (FAL)

#3 - 2015-01-09 20:40 - Mathias Schreiber

- Target version set to 7.1 (Cleanup)
- Sprint Focus set to On Location Sprint

#4 - 2015-01-09 20:43 - Markus Klein

IMO using getPublicUrl() for internal further processing is just plain wrong. Does not work for protected storages I guess and will for sure not work if there's some other driver than the LocalDriver.

#5 - 2015-01-09 22:45 - Peter Niederlag

Markus Klein wrote:

IMO using getPublicUrl() for internal further processing is just plain wrong. Does not work for protected storages I guess and will for sure not work if there's some other driver than the LocalDriver.

I do very much agree, but what's the alternative? GifBuilder relies on ContentObjectRenderer->getImgResource(), that doesn't seem debatable to me. However this will add 'originalFile' in case of an fileObject so maybe GifBuilder should pick up on that on if it's available?

2015-08-04 3/5

#6 - 2015-01-14 22:57 - Frans Saris

Ear proposing	a fila uca	antEarl and Dr	accoring() and	l not antDublial Irl/\
rui piucessiiiq	a lile use	ueiroilocairi	ocessinan and	l not getPublicUrl().

#7 - 2015-01-17 07:26 - Torben Hansen

Frans Saris wrote:

For processing a file use getForLocalProcessing() and not getPublicUrl().

Using getForLocalProcessing() seems to work fine if we directly use it in GifBuilder

 $\theta = \frac{1}{2} - \frac{1}{2}$

Should there be a check to see, if \$fileInfo['originalFile'] is really available?

#8 - 2015-01-19 09:49 - Peter Niederlag

Hi,

first of all, many thx for your initiative.

Torben Hansen wrote:

Frans Saris wrote:

For processing a file use getForLocalProcessing() and not getPublicUrl().

Using getForLocalProcessing() seems to work fine if we directly use it in GifBuilder

[...]

Should there be a check to see, if \$fileInfo['originalFile'] is really available?

If GIFBUILDER can still work without FAL (which I think is true), then there must be a check if originalFile is available. Should not be to expensive and is just making this beast less error prone.

#9 - 2015-01-22 20:05 - Gerrit Code Review

- Status changed from New to Under Review

Patch set 1 for branch master of project Packages/TYPO3.CMS has been pushed to the review server.

It is available at http://review.typo3.org/36180

#10 - 2015-01-22 21:30 - Gerrit Code Review

2015-08-04 4/5

 $\textbf{Patch set 2 for branch \textbf{master} of project \textbf{Packages/TYPO3.CMS} \ has been pushed to the review server.}$

It is available at http://review.typo3.org/36180

#11 - 2015-01-29 08:25 - Gerrit Code Review

Patch set 1 for branch TYPO3_6-2 of project Packages/TYPO3.CMS has been pushed to the review server. It is available at http://review.typo3.org/36340

#12 - 2015-01-29 08:30 - Torben Hansen

- Status changed from Under Review to Resolved
- % Done changed from 0 to 100

Applied in changeset commit:fd232edeab2c72a7bac582b454b8db6b788f017c.

2015-08-04 5/5