

Fluid - ViewHelper - Incubator - Suggestion # 6526

Status:	Needs Feedback	Priority:	Should have
Author:	Nils Blattner	Category:	
Created:	2010-02-19	Assigned To:	
Updated:	2010-10-20	Due date:	
Has patch:			
Tags:			
Subject:	cdata		
Description			
<p>Simple, yet essential ViewHelper if you want to print out CDATA content (as fluid removes the CDATA start/end tags and just prints the content).</p>			
<pre>/* ** This script is part of the TYPO3 project - inspiring people to share! ** ** TYPO3 is free software; you can redistribute it and/or modify it under ** the terms of the GNU General Public License version 2 as published by ** the Free Software Foundation. ** ** This script is distributed in the hope that it will be useful, but ** WITHOUT ANY WARRANTY; without even the implied warranty of MERCHAN- ** TABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General ** Public License for more details. ** */ /** * @package Fluid * @subpackage ViewHelpers * @version \$Id: CropViewHelper.php 1734 2009-11-25 21:53:57Z stucki \$ */ /** * Use this Helper if you need to print <![CDATA[]]. * @version \$Id:\$ * @license http://opensource.org/licenses/gpl-license.php * GNU Public License, version 2 * @scope prototype */ class Tx_CabagSteps_ViewHelpers_CdataViewHelper extends Tx_Fluid_Core_ViewHelper_AbstractViewHelper { /** * Render the CDATA content. * * @return string CDATA comment * @author Nils Blattner <nb@cabag.ch> */ public function render() { return '<![CDATA[' . \$this->renderChildren() . ']]>'; } } ?></pre>			

History

#1 - 2010-02-20 22:04 - Tommy Seus

I think it is still necessary to set a variable so that the content will not be changed.

This prevents the double quotes are converted.

```
protected $objectAccessorPostProcessorEnabled = FALSE;
```

#2 - 2010-07-04 00:01 - Christian Müller

- Status changed from New to Needs Feedback

Couldn't that be done with just using the RawViewHelper? You just put the CDATA opener and closer into a RawViewHelper. Any content inside that shouldn't be parsed could be enclosed by RawViewHelper.

#3 - 2010-07-07 00:11 - Nils Blattner

Haven't actually tested it that way, but consider that the cdata tag would probably be removed if put into the body.

Might work if you use it like `<x:raw raw="<![CDATA[...]]>" />`, but then you cannot render stuff into it by encapsulating viewhelpers.

Which is what I needed when I was creating KML-Files (geodata xml).

#4 - 2010-07-12 12:18 - Bastian Waidelich

- Tracker changed from Feature to Suggestion

- Project changed from TYPO3.Fluid to Fluid - ViewHelper - Incubator

#5 - 2010-07-12 13:14 - Bastian Waidelich

- Subject changed from CDATA ViewHelper to cdata