

## TYPO3.Flow - Bug # 6680

<b>Status:</b>	Closed	<b>Priority:</b>	Must have
<b>Author:</b>	Thomas Fritz	<b>Category:</b>	Environment
<b>Created:</b>	2010-03-03	<b>Assigned To:</b>	Karsten Dambekalns
<b>Updated:</b>	2010-10-20	<b>Due date:</b>	
<b>PHP Version:</b>			
<b>Has patch:</b>			
<b>Complexity:</b>			
<b>Affected Flow version:</b>			
<b>Subject:</b>	Make FLOW3 open_basedir aware		
<b>Description</b>			
<p>FLOW3 uses the Default Temporary Path for the Operating Systems. In Linux '/tmp' is used for different operations. This behaviour triggers an error on environments where a open_basedir ini setting was set.</p> <p>Perhaps it is better to use a Path within the FLOW3 Root Path in 'Data/Temporary' or determine the temporary path out of upload_tmp_dir or session_save_path ini setting.</p>			

### History

#### #1 - 2010-03-06 00:16 - Karsten Dambekalns

- Category set to Environment
- Status changed from New to Closed
- Assigned To set to Karsten Dambekalns
- Target version set to 1.0 alpha 8

The Environment class provides a method to get the temporary directory. That by default uses the Data/Temporary folder. The use of /tmp is a fallback. So, we try to do what you want, but if that doesn't work, we need to fall back to something. Make sure you have the permissions set correctly.