Task # 27561 (Accepted): Complete documentation

Status: **Under Review Priority:** Could have Author: Thomas Fritz Category: - Documentation -Created: 2010-07-18 Assigned To: Christian Müller Updated: Due date: 2014-06-19 Sprint: PHP Version: Has patch: No Complexity:

Subject: Provide a Nginx Server Configuration for FLOW3

Description

Provide or let the FLOW3 CLI generate a Nginx (or Apache) server configuration file or document it how one can use FLOW3 with nginx.

This is the main FLOW3 server configuration. On my blog i have posted the other configuration files needed:

 $\underline{\text{http://fritzthomas.com/php/600-how-to-use-flow3-with-nginx-working-server-configuration/}}$

The only part i could not test are the "_Resources/Persistent" Urls. But they should work.

```
server {
                80:
    listen
                    flow3.local *.flow3.local;
     server name
               /var/www/test/flow3/Web;
     root
     autoindex
                  off;
     access log
                   /var/www/test/logs/access.log combined;
                  /var/www/test/logs/error.log info;
     error_log
     location ~ "^/ Resources/Persistent/" {
         rewrite "^(_Resources/Persistent/.{40})/.+(\..+)" /$1$2 break;
    }
     location ~ "^/_Resources/" {
         access log off;
         log_not_found off;
         expires max;
         break;
    }
    location / {
         rewrite ".*" /index.php last;
    }
     location = /index.php {
          #fastcgi param FLOW3 CONTEXT
                                                    Development;
         fastcgi param FLOW3 CONTEXT
                                                    Production;
         fastcgi param FLOW3 REWRITEURLS
                                                       1;
         fastcgi intercept errors on;
         fastcgi_split_path_info ^(.+\.php)(/.+)$;
         include includes/fastcgi_params;
```

2015-08-03 1/6

```
# "Upstream" defined in nginx.conf
fastcgi_pass php-5.3.2;
}
}
```

Related issues:

related to TYPO3.Flow - Feature # 8981: Security/Performance: Provide Webserv...

New 2010-07-21

related to TYPO3.Flow - Task # 27573: Update installation documentation

Resolved 2011-06-20

related to Core - Task # 54316: Provide a Nginx server configuration

New 2013-12-11

History

#1 - 2010-07-21 16:23 - Thomas Fritz

It should read above: "The only part i could not test are the "_Resources/Persistent" Urls. But they should work.":)

#2 - 2010-08-18 15:09 - Karsten Dambekalns

- Category set to - Documentation -

#3 - 2011-01-26 09:45 - Oliver Wand

Since I switched to Nginx on my Mac I wanted to adapt nginx.conf for FLOW3 (1.0.0-alpha14) to my needs.

The above blog bost didn't work for my configuration based on Nginx 0.8.54 (Macport installation) with PHP 5.3.5 on Mac OS 10.6.6.

What finally got me up and running - in addition to the above posting - was this forum entry: http://forum.nginx.org/read.php?2,866,30886

So here's the flow3.conf I included to my nginx.conf:

```
server {
    listen
                80:
                     flow3.local *.flow3.local;
    server_name
                /usr/local/html/FLOW3/Web;
    root
    autoindex
                    /usr/local/var/log/nginx/access.log combined;
    access_log
    error_log
                  /usr/local/var/log/nginx/error.log info;
    location ~ "^/_Resources/Persistent/" {
         rewrite "^(Resources/Persistent/.{40})/.+(\...+)" /$1$2 break;
    }
    location ~ "^/_Resources/" {
         access_log off;
         log_not_found off;
         expires max;
         break;
    }
    location / {
         rewrite ".*" /index.php last;
```

2015-08-03 2/6

```
}
        location ~ ^(.+\.php)(.*)$ {
            fastcgi_pass 127.0.0.1:9000;
            fastcgi_index index.php;
            fastcgi_param FLOW3_CONTEXT
                                                   Development;
            fastcgi_param FLOW3_REWRITEURLS
                                                       0;
            fastcgi_intercept_errors on;
            fastcgi_split_path_info ^(.+\.php)(.*)$;
            fastcgi_param SCRIPT_FILENAME /usr/local/html/FLOW3/Web$fastcgi_script_name;
            fastcgi_param PATH_INFO
                                           $fastcgi_path_info;
            include /usr/local/etc/nginx/fastcgi_params;
        }
   }
#4 - 2011-06-20 11:02 - Karsten Dambekalns
```

- Parent task set to #27561

#5 - 2011-06-21 16:29 - Karsten Dambekalns

- Status changed from New to Accepted
- Assigned To set to Karsten Dambekalns
- Target version set to 1230

#6 - 2011-08-24 07:44 - Karsten Dambekalns

- Subject changed from Provide a Nginx Server Configuration for flow3 to Provide a Nginx Server Configuration for FLOW3

#7 - 2011-08-24 08:04 - Karsten Dambekalns

- Tracker changed from Feature to Task

#8 - 2011-10-20 01:43 - Karsten Dambekalns

- Target version deleted (1230)

#9 - 2012-02-29 16:56 - Martin Brüggemann

- Has patch set to No

I had to modify the resource url regexp like this to get it working:

```
location ~ "^/_Resources/Persistent/" {
 rewrite \ "(.\{40\})/.+(\...+)"\ /\_Resources/Persistent/\$1\$2\ break;
}
```

#10 - 2012-05-24 11:10 - Bastian Waidelich

This is what we use for http://t3con12-asia.typo3.org/ right now for persistent resources (thanks to Steffen Gebert):

```
location ~ "^/ Resources/Persistent/" {
  access_log off;
  log_not_found off;
```

2015-08-03 3/6

#11 - 2012-07-04 10:43 - Karsten Dambekalns

- Assigned To changed from Karsten Dambekalns to Christian Müller

#12 - 2012-07-04 10:43 - Karsten Dambekalns

- Target version set to 1.1

#13 - 2012-08-17 11:19 - Karsten Dambekalns

- Target version changed from 1.1 to 1.1.1

#14 - 2012-08-27 18:04 - Christian Müller

Just as addition, I will compile all the info here into something final for docs. This is the rewrite config used in the conference websites:

```
location ~ "^/_Resources/Persistent/" {
    access_log off;
    log_not_found off;
    expires max;

rewrite "(.{40})/.+\.(.+)" /_Resources/Persistent/$1.$2 break;
    rewrite "([a-z0-9]+/(.+/)?[a-f0-9]{40})/.+\.(.+)" /_Resources/Persistent/$1.$2 break;
}
```

#15 - 2012-10-10 18:34 - Christian Müller

If you are working with master take care that the settings are now called FLOW_XXXXX instead of FLOW3_XXXXX

#16 - 2012-10-19 17:41 - Rafael Kähm

If you want to run some PHP-Applications like <u>www.your-domain.dev/roundcubemail/</u>, you must stop rewriting by existing files in TYPO3-Flow/Web(also document root).

here is my setup for TYPO3-Flow 1.1.0 and/or TYPO3-Neos Alapha1

```
server {
    listen *:80;
    server_name www.your-domain.dev;
    root /var/www/TYPO3-Flow/Web;
    index index.html index.htm index.php index.xhtml;
    error_log /var/log/httpd/www.your-domain.dev/error.log;
```

2015-08-03 4/6

```
## Disable .htaccess and other hidden files
location ~ ∧. {
  deny all;
  access_log off;
  log_not_found off;
location = /favicon.ico {
  log_not_found off;
  access_log off;
}
location = /robots.txt {
  allow all;
  log_not_found off;
  access_log off;
location /_Resources/ {
  access_log off;
  log_not_found off;
  expires max;
  break;
}
location /_Resources/Persistent/ {
  access_log off;
  log_not_found off;
  expires max;
  rewrite "(.{40})/.+\.(.+)" /_Resources/Persistent/$1.$2 break;
  }
###
# stop rewriting by existing files | is instead of -> location / { rewrite ".*" /index.php last; }
# use this if you want to run other PHP-Applications in TYPO3-Flow/Web directory
###
try_files $uri $uri/ /index.php?$args;
location ~ \.php$ {
  include /etc/nginx/fastcgi_params;
  fastcgi_pass 127.0.0.1:9012;
  fastcgi_index index.php;
  ###
  # for FLOW3 <= 1.1.x only | see note #15 on http://forge.typo3.org/issues/8923
  fastcgi_param FLOW3_CONTEXT
                                         Development;
  # fastcgi_param FLOW3_CONTEXT
                                           Production;
  fastcgi_param FLOW3_REWRITEURLS
                                           1;
```

2015-08-03 5/6

```
###
          # Make sure that you set the environment vars for new versions \
          # of TYPO3-XXXXX(TYPO3-Neos) products properly
          # see note #15 on http://forge.typo3.org/issues/8923
          ###
          # fastcgi_param FLOW_CONTEXT
                                                  Development;
          ## fastcgi_param FLOW_CONTEXT
                                                    Production;
          # fastcgi_param FLOW_REWRITEURLS
                                                     1;
          fastcgi_split_path_info ^(.+\.php)(.*)$;
          fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;
          fastcgi_param PATH_INFO
                                        $fastcgi_path_info;
          fastcgi_buffer_size
                                  128k;
          fastcgi buffers
                                256 16k;
          fastcgi_busy_buffers_size 256k;
          fastcgi_temp_file_write_size 256k;
          fastcgi_read_timeout
                                   240; ### set this value for your server
   }
#17 - 2012-12-14 15:09 - Karsten Dambekalns
- Target version changed from 1.1.1 to 2052
#18 - 2013-08-14 15:40 - Karsten Dambekalns
- Target version changed from 2052 to 1.1.1
#19 - 2014-02-25 00:36 - Simon Schaufelberger
any update here? what's blocking to put that in the repository?
#20 - 2014-03-12 23:03 - Michiel Roos
Bump!
```

Patch set 1 for branch **master** of project **Packages/TYPO3.Flow** has been pushed to the review server. It is available at https://review.typo3.org/30398

#21 - 2014-05-26 14:44 - Gerrit Code Review - Status changed from Accepted to Under Review

2015-08-03 6/6